

Analytical and numerical  
homogenization of  
Channeline GRP structural  
liners for various geometries

Dr. Dev Chelot  
Head of Quality and R&D




## Rehabilitation work in sewage industry

- The existing sewers consists of culverts, bricks, stones, concretes, etc.
- Issues: Effects of  $H_2S$  attack, corrosion, structural loading beyond its capability.
- Rehabilitating sewers is necessary for such scenarios.



## Why Composite materials (GRP)?


- Choice of Resins: Polyester, Vinyl Ester, Epoxy resin
- Multi-functional capabilities
  - Structural
  - Chemical Resistant
  - Light Weight
- Flexible Pipes: Reduced brittle damage
- Can be custom fabricated to any size, shape or form using hand layup method.
- Cost effective Transportation



## Problems Associated with unitary pipes


- ⑩ Access to drop large diameter pipes
- ⑩ Time consuming
- ⑩ Expensive task

Access to the Sewer



## Solution: Unitary $\Rightarrow$ Multi- Piece

Transportation





## Unitary ⇒ Multi-Piece

### Issues specific to Multi-piece pipes


- Usage of the right adhesive
- Mechanical stiffness and strength reduction at joints.
- Corrosive damage to the inside of the pipe



## Assembling of multi-segmental pipes



## Loading Conditions on a Sewer Pipe



### Mechanical Loads:


- Bending
- Tension
- Compression
- Stiffness
- Hoop


## Ring stiffness test / Parallel plate test

### Standard: ASTM D2412 Specification



- Ring stiffness test involves ascertaining whether GRP pipes can maintain their shape and structural integrity when exposed to various loads.
- **Deflection rate:** 12.5mm/min (as per ASTM D2412)
- **Length of the specimen:**  
300mm (+/- 5mm) for ID/H < 1524mm  
20% of the ID/H for ID/H > 1524mm

$$PS = \frac{\frac{Max\ Load\ at\ 5\% \ deflection}{Length\ of\ the\ specimen}}{Deflection\ in\ (mm)}$$









Shapes	Dimension
Circular Pipe 1 (CP1) & Three-Piece Circular (CP1-3)	Internal Diameter: 2200[mm] Length: 440[mm] Wall Thickness 32[mm]
Circular Pipe 2 (CP2) & Four-Piece Circular (CP2-4)	Internal Diameter: 4876.80[mm] Length: 975.36[mm] Wall Thickness 90[mm]
Box Pipe (BP) & Two-Piece Box (BP-2)	Height: 316[mm] Width: 536[mm] Length: 305[mm] Wall Thickness: 25.4[mm]
Semi Elliptical Pipe (SEP) & Two-Piece Semi Elliptical (SEP-2)	Height: 1346.2[mm] Width: 1541.78[mm] Length: 305[mm] Wall Thickness: 28[mm]



Pipe Type	Load (kN) at 5% deflection	Stiffness (MPa)
CP1 (Unitary)	11.02	0.22
CP1-3 (Three-piece)	15.53	0.32
CP2 (Unitary)	62.40	0.26
CP2-4 (Four-piece)	69.59	0.30
BP (Unitary)	20.61	4.29
BP-2 (Two-piece)	22.39	4.70
SEP (Unitary)	7.04	0.34
SEP-2 (Two-piece)	11.60	0.56




## Conclusion of the Ring Stiffness test results

- Box-shaped pipes demonstrates highest stiffness in comparison to circular and semi-elliptical shaped pipes.
- Multi-piece pipes **show equal or higher stiffness** than one-piece pipes.
- Two-piece box-shaped pipes demonstrate the **highest stiffness**.
- FEA shows good accuracy particularly for Box culvert profile and Semi Elliptical profile.

## Case study: Rehabilitation of Northeast-Interceptor East Arm (NIEA), Detroit

- Located in Oakland and Macomb county, north of Detroit City
- System was constructed in 6 contract sections between 1969 and 1978
- Approximate length of 79,380 LF
- Ranging in diameter from 12' to 17' 6"
- Traditional Rib and Lagging Tunnel construction with a concrete cast in place secondary liner



## Case study: Rehabilitation of Northeast-Interceptor East Arm (NIEA), Detroit

- The new GRP liner has an ID of 16' (4876.8mm) and a wall thickness of 3.54" (90mm) in accordance with AWWA M45 design.
- Prototype pipes were manufactured, and all jointing systems were fully tested for strength, integrity and leak tightness in accordance with relevant ASTM Standards



## Case study: Rehabilitation of Northeast-Interceptor East Arm (NIEA), Detroit


- Moulds are all built specifically for each individual project
- All liners were manufactured under strict QA/QC guidelines in accordance with ASTM D3262
- Full Inspection Test Procedure Reports were compiled for each Lot and submitted to the owner once the lot was complete.



- After the manufacturing and finishing process was completed, the liner was crated and loaded into 40ft Seacans.



- Installation was constructed using a custom designed Pipe Robotic Pipe Carrier.
- The carrier is multi function System that is operated from an Integrated cockpit.
- The system has pipe re-rounders to ensure that each pipe is not deflected under its own weight.
- The carrier also has a forward working platform so that work crews can reach the crown of the pipe to install wooden blocking etc.







# Approvals and certifications for Channeline

BOARD OF PUBLIC WORKS  
ADRIÀ GARCIA  
PRESIDENT  
M. TERESA VILLEGRAS  
VICE PRESIDENT  
DR. MICHAEL R. DAVIS  
PRESIDENT PRO TEMPORE  
VAOZ KHORSHID  
COUNSELOR  
SUSAN REYES  
COMMISSIONER  
TJ COOK  
ACTING CHIEF FINANCIAL OFFICER



DEPARTMENT OF  
PUBLIC WORKS  
BUREAU OF  
ENGINEERING  
TED ALLEN, PE  
CITY ENGINEER  
1148 S. BROADWAY, SUITE 700  
LOS ANGELES, CA 90015-2213  
http://eng.lacity.org

February 22, 2023  
(Revised 9/19/24)

Tim Webb  
Channeline International  
P.O. Box 8091  
Dubai Investment Park, PH-2  
Dubai, U.A.E.

## SUBJECT: CHANNELINE CLASS "R" RPMP APPROVAL

BD002853

Dear Mr. Webb,

Channeline Class "R" Reinforced Polymer Mortar Pipe (RPMP) is approved for City-wide use. The approved methods are slip-lining and transport-into-place. This approval shall expire on Feb 23, 2027, at which time recertification is required. You may apply for a four-year extension of this approval 120 days before it expires. Please maintain a copy of this approval for your records.

### Conditional Approval for Pipes with Inside Diameter or Vertical Height from 32" -

1. There shall be no change in materials or manufacturing plant location
2. Installation is subject to inspection by Bureau of Contract Administration
3. Testing shall be performed per specification section 02570 "Reinforced Polymer Concrete Pipe (RPMP)" and meet the material property values found herein

### A. Approved materials of construction:

1. Inner liner required for: 60 mils thick Dow Denbrane 411, Vinyl Ester Resin, or Scott Bader Crystic VE 671 PA, Vinyl Ester Resin, C-glass tissue for barrier layup
2. Body resin: A.O.C. DCPD Resin H934-CEA
3. Body aggregate: Surface Tissue, 30 gr/m<sup>2</sup>
4. Glass reinforcement: Chopped Strand Mat, 450 gr/m<sup>2</sup> (Unidirectional), 600 gr/m<sup>2</sup>
5. Approved manufacturing plant: Dubai, U.A.E.
6. Approved size range: Inside diameter or vertical height: 38" to 118" (for less than 38", see conditional approval above)
7. Joints: Gasketed for sliplining per ASTM D4161 Filled with sealant for person entry installations

AN EQUAL OPPORTUNITY EMPLOYER



Organisme certificateur  
Certification body

## Certificat

Assainissement  
Réseaux - Réhabilitation de réseaux  
CLASS R

Le CSTB atteste que le produit ci-dessus est conforme à des caractéristiques décrites dans le référentiel de certification OB 09 Assainissement en vigueur après évaluation selon les modalités de contrôle définies dans ce référentiel.

En vertu de la présente décision, le CSTB accorde à :

La société CHANNELINE INTERNATIONAL FIBER GLASS MANUFACTURING LLC  
PO BOX 8091 Dubai Investment Park, PH2 AE - DUBAI

Unité

le droit d'usage de la marque OB 09 Assainissement pour le produit objet de cette décision, pour toute sa durée de validité et dans les conditions prévues par les exigences générales de la marque OB et le référentiel mentionné ci-dessus.



26-01-294-V2

### CARACTÉRISTIQUES CERTIFIÉES

Conformité à l'avis Technique n°17.2/15-296/V2

-Caractéristique de Durabilité  
-Caractéristiques matières

-Caractéristique de mise en œuvre  
-Caractéristiques dimensionnelles

- Flexion à court terme
- Flexion à long terme
- Traction

Ce certificat comporte 1 page.  
Consignes de lecture:  
Marie-Claire TROUILLE  
Courriel : marie-claire.troulle@cstb.fr  
Tél. : 01 64 68 92 81



Roland BASSÉ

CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT  
84 avenue Jean-Jaurès - Champs-de-Marne - 77140 Marne-la-Vallée cedex 2  
Tél. +33 (0)1 64 68 92 81 - Fax : +33 (0)1 64 68 94 94 - www.cstb.fr  
MARNE LA-VALLÉE / PARIS / GRENOBLE / NANTERRE / SOPHIA ANTIPOLIS



cofrac



QB



BCCA



## BENOR CERTIFICATE

Issued on the basis of the provisions of the Implementation Rules for BENOR certification of thermoplastic pipes and accessories, TRA BB 652, to the company

Channeline International Fiber Glass Manufacturing  
L.L.C.  
P. O. Box 8091, Dubai, AE - Abu Dhabi

for the production of

Monolithic circular and non-circular glass-reinforced thermosetting plastics (GRP) elements for sewer rehabilitation covering the entire surface of the sewer (without pressure); Channeline

manufactured in the production unit

Channeline International Fiber Glass Manufacturing L.L.C.  
P. O. Box 8091, Dubai, AE - Abu Dhabi

in accordance with the

PTB BB-652-100: 2014 "Thermosetting plastics piping systems for sewer rehabilitation (without pressure) - Circular and non-circular elements made of GRP; monolithic elements covering the entire inner surface of the sewer"

By issuing the certificate, BCCA declares that, on the basis of (I) the initial assessment of the product characteristics by means of testing; (II) the initial evaluation and acceptance of the quality assurance in production; (III) the regular external control of the quality of the product, the product is in accordance with the requirements of the standard and the applicable external laboratory, sufficient confidence can be given to the measures taken by the certificate holder for guaranteeing conformity with the prescriptions.

The BENOR mark certifies that the certificate holder gives the data with regard to the certified product. This document is an annex to the certificate and is authenticated by BCCA.

Following the issue of this certificate and as long as it is maintained valid, BCCA grants the right to use the BENOR mark to the certificate holder. The use of the BENOR mark is governed by a suitable identification of the product.

The use of the BENOR mark does not relieve the certificate holder of his responsibilities with regard to the delivered product.

The validity of this certificate can be checked via [www.bcca.be](http://www.bcca.be).

N° certificate BB-652-472-652-2-472-39308 | Valid from 2024-05-30 until 2027-05-29

Issued in Brussels, on 2 July 2024.

Olivier DELEROUCK  
General Manager

The BENOR mark is a registered collective mark, that is to say the property of the Chamber of Commerce and Industry of Brussels and the Flemish Region (BCCA). The BENOR certificate is a voluntary system that is established on the basis of a quality assurance in production. The BENOR mark is granted to products that are produced in accordance with the requirements of the standard. The BENOR mark does not relieve the certificate holder of his responsibilities with regard to the delivered product.

The validity of this certificate can be checked on the website [www.bcca.be](http://www.bcca.be). Further information regarding the scope of this certificate and the applicability of the requirements of the standard may be obtained from the certificate holder.

BELGIAN CONSTRUCTION CERTIFICATION ASSOCIATION NPO  
HEADQUARTERS: CANTIEREN, 47 BE - 1000 BRUSSELS  
COURT OF APPEAL: COURTRIÉ, COURTRAI, COURTRAY, HERMELINNE, JEMEPPE  
TEL. + 32 2 236 24 01 | WWW.BCCA.BE  
MAIL: [BOCCABE.1@WILM.BE](mailto:BOCCABE.1@WILM.BE)





## Approvals and certifications for Channeline



[www.channeline.com](http://www.channeline.com)

## Channeline multi-segmental projects

- NIEA, Detroit, Michigan
- City of Boston, Stoughton
- City of Los Angeles, California





# Thank you - any questions?

## Get in touch

Email: [tim.webb@channeline.com](mailto:tim.webb@channeline.com);  
[dev@channeline.com](mailto:dev@channeline.com)

Website: [www.channeline.com](http://www.channeline.com)